## CERTIFICATE OF COMPLIANCE

Certificate Number E357031

Report Reference E357031-20170913

Issue Date 2020-JUNE-15

Issued to: Bridgelux Inc

46430 Fremont Blvd Fremont CA 94538

This certificate confirms that representative samples of

COMPONENT - LIGHT-EMITTING-DIODE ARRAYS,

MODULES AND CONTROLLERS

See next page

Have been investigated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete

in certain constructional features or restricted in

performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 8750 Light Emitting Diode Light Sources for use in

Lighting

CAN/CSA C22.2 No. 250.13-17 Light Emitting Diode

**Equipment for Lighting Applications** 

Additional Information: See the UL Online Certifications Directory at

https://iq.ulprospector.com for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Recognized Component Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

Bambles

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <a href="http://ul.com/aboutul/locations/">http://ul.com/aboutul/locations/</a>



# CERTIFICATE OF COMPLIANCE

Certificate Number E357031

Report Reference E357031-20170913

Issue Date 2020-JUNE-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

#### Models

USR, CNR – LED Modules, Vesta TL Series, models BXEB-TL-abcde-100i-j-kl, BXEB-TL-abcde-300i-j-kl, BXEB-TL-L1120, BXEB-TL-L0560, and BXEB-TL-L0280as described under nomenclature.

#### MODEL NOMENCLATURE:

Vesta TL Series,

BXEB-TL-abcde-fghi-j-kl where:

### BXEB - Product Family

TL - tunable linear

abcd - alphanumeric characters designate nominal ANSI color temperature range

e – alphanumeric character designates minimum CRI

fghi – alphanumeric characters designate nominal flux/form factor, when fgh is 100 it designates the 1' with 96 LED model and when fgh is 300 it designates the 2' with 192 LED model

j – alphanumeric character designates electrical configuration

k – alphanumeric character designates product generation

I – alphanumeric character designates CCT bin option

and

BXEB-TL-Lxxxxa-bcdefgh-j-ik where:

BXEB - Product Family

TL - tunable linear

Lxxxx - PCB length in cm (L0280-280mm, L0560-560mm, or L1120-1120mm)

a – alphanumeric character designates width

bc - alphanumeric characters designate nominal ANSI color temperature

d – alphanumeric character designates minimum CRI
 efgh – alphanumeric character designates nominal flux

j – alphanumeric characters designate SMD configuration
i – alphanumeric character designates product version

k – alphanumeric character designates CCT bin option



Bruce Mahrenholz, Director North American Certification Program

UL LLC



