

## 650V 20A N-Channel Enhancement Mode Power MOSFET


### General Description

BXP20N65 is Bridgelux high voltage MOSFET family based on advanced planar DMOS technology. This advanced MOSFET family has optimized on-state resistance, and also provides superior switching performance and higher avalanche energy strength. This device family is suitable for high efficiency switch mode power supplies.

### FEATURES

- $R_{DS(on)} \leq 0.4 \Omega$  @  $V_{GS}=10V$ ,  $I_D=10A$
- Low  $C_{rss}$
- Ultra Low gate Charge
- Fast switching capability
- Improved  $dv/dt$  capability

### SYMBOL



TO-220



TO-220F

### ASSEMBLY MESSAGE

Product Name	Package	Packaging
BXP20N65P	TO-220	Tube
BXP20N65F	TO-220F	Tube

### ABSOLUTE MAXIMUM RATINGS ( $T_C=25^\circ\text{C}$ unless otherwise noted)

Parameter		Symbol	Rating		Unit
			BXP20N65P	BXP20N65F	
Drain-Source Voltage		$V_{DS}$	650		V
Drain Current	Continuous ( $T_C = 25^\circ\text{C}$ )	$I_D$	20		A
	Continuous ( $T_C = 100^\circ\text{C}$ )		13		A
Drain Current	Pulsed (Note1)	$I_{DM}$	80		A
Gate-Source Voltage		$V_{GS}$	$\pm 30$		V
Avalanche Energy	Single Pulse (Note2)	$E_{AS}$	1350		mJ
Avalanche Current (Note1)		$I_{AR}$	3.2		A
Peak Diode Recovery $dv/dt$ (Note3)		$dv/dt$	5		V/ns
Power Dissipation (Note 2)	$T_C = 25^\circ\text{C}$	$P_D$	235.8	80	W
	Derate above $25^\circ\text{C}$		1.89	0.64	W/ $^\circ\text{C}$
Maximum Junction Temperature		$T_J$	150		$^\circ\text{C}$
Storage Temperature Range		$T_{STG}$	-55 to 150		$^\circ\text{C}$

- Note:**
1. Repetitive Rating: Pulse width limited by maximum junction temperature
  2.  $L=10\text{mH}$ ,  $V_{DD}=50\text{V}$ ,  $R_G=25 \Omega$ , Starting  $T_J = 25^\circ\text{C}$
  3.  $I_{SD} \leq 20\text{A}$ ,  $di/dt \leq 200\text{A}/\mu\text{s}$ ,  $V_{DD} \leq BV_{DS}$ , Starting  $T_J = 25^\circ\text{C}$

## THERMAL CHARACTERISTICS

Parameter	Symbol	Max.		Unit
		BXP20N65P	BXP20N65F	
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	0.53	1.56	°C / W

## ELECTRICAL CHARACTERISTICS (T<sub>J</sub>=25°C, unless otherwise Noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	VGS=0V, ID=250μA	650			V
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	VDS=650V, VGS=0V			1	uA
		VDS=520V, TC = 125°C			100	uA
Gate-Body Leakage Current, Forward	I <sub>GSS</sub>	VGS=30V			100	nA
Gate-Body Leakage Current, Reverse		VGS=-30V			-100	nA
Breakdown Voltage Temperature Coefficient	△BVDSS/ △TJ	ID = 250 μA		0.5		V/°C
ON CHARACTERISTICS						
Gate Threshold Voltage	V <sub>GS(TH)</sub>	VDS=VGS, ID=250μA	2	3	4	V
Drain-Source On-State Resistance	R <sub>DS(ON)</sub>	VGS=10V, ID=10A		0.35	0.4	Ω
Forward Trans conductance (Note4)	g <sub>FS</sub>	VDS = 15V, ID=10A		17		S
DYNAMIC PARAMETERS						
Input Capacitance	C <sub>ISS</sub>	VDS=25V, VGS=0V, f=1.0MHz		2560		pF
Output Capacitance	C <sub>OSS</sub>			420		pF
Reverse Transfer Capacitance	C <sub>RSS</sub>			50		pF
SWITCHING PARAMETERS						
Turn-ON Delay Time	t <sub>D(ON)</sub>	VDD=325V, ID=20A, VGS = 10V ,RG=25Ω (Note4,5)		40		ns
Turn-ON Rise Time	t <sub>R</sub>			90		ns
Turn-OFF Delay Time	t <sub>D(OFF)</sub>			188		ns
Turn-OFF Fall-Time	t <sub>F</sub>			80		ns
Total Gate Charge(Note5)	Q <sub>G</sub>	VDD =325V, VGS =10V, ID =20A (Note4,5)		61		nC
Gate Source Charge	Q <sub>GS</sub>			13		nC
Gate Drain Charge	Q <sub>GD</sub>			24		nC
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Drain-Source Diode Forward Voltage	V <sub>SD</sub>	IS=20A, VGS=0V			1.5	V
Diode Continuous Forward Current	I <sub>S</sub>				20	A
Pulsed Drain-Source Current	I <sub>SM</sub>				80	A
Reverse Recovery Time	t <sub>RR</sub>	VGS = 0 V, ISD = 20A		410		ns
Reverse Recovery Charge	Q <sub>RR</sub>	di/dt=100 A/μs (Note4,5)		3.9		uC

Note: 4. Pulse Test : Pulse width ≤ 300μs, Duty cycle ≤ 2%

5. Essentially independent of operating temperature

## TYPICAL CHARACTERISTICS




Figure1. Typical Output Characteristics




Figure2. Typical Transfer Characteristics




Figure3. On-Resistance versus Drain Current




Figure4. Diode forward voltage versus Current




Figure5. Typical Capacitance versus  $V_{DS}$




Figure6. Typical Gate Charge versus  $V_{GS}$

# TYPICAL CHARACTERISTICS(Cont.)




Figure7.  $BV_{DSS}$  Variation with Temperature




Figure8. On-Resistance Variation with Temperature




Figure9. Maximum Safe Operating Area  
BXP20N65P




Figure10. Maximum Safe Operating Area  
BXP20N65F






Figure10. Maximum Continuous Drain Current  
versus Case Temperature


## TEST CIRCUITS AND WAVEFORMS




Gate Charge Test Circuit



Gate Charge Waveform




Resistive Switching Test Circuit




Resistive Switching Waveforms


## TEST CIRCUITS AND WAVEFORMS(Cont.)




### Diode Reverse Recovery Test Circuit



### Diode Reverse Recovery Waveform



### Unclamped Inductive Switching Test Circuit



### Unclamped Inductive Switching Waveforms

## Revision history

### Document revision history

Date	Revision	Changes
17-Jan-2022	1.0	First release

**Disclaimers:**

Bridgelux WuXi has made reasonable commercial efforts to ensure that the information given in this data sheet is correct. However, it must clearly be understood that such information is for guidance only and does not constitute any representation or form part of any offer or contract.

For documents and material available from this data sheet, Bridgelux WuXi does not warrant or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, product, technology or process disclosed hereunder.

Bridgelux WuXi reserves the rights to at its own discretion to make any changes or improvements to this data sheet. Unless said data sheet is incorporated into the formal contract, any customer should not rely on the information as any specification or product parameters duly committed by Bridgelux WuXi. Customers are hereby advised to verify that the information contained herein is current and complete before the entering of any contract or acknowledgement of any purchase order. Accordingly, all products specified hereunder shall be sold subject to Bridgelux WuXi's terms and conditions supplied at the time of order acknowledgement. Except where agreed upon by contractual agreement, testing of all parameters of each product is not necessarily performed.

Bridgelux WuXi does not warrant or convey any license either expressed or implied under its patent rights, nor the rights of others. Reproduction of information contained herein shall be only permissible if such reproduction is without any modification or alteration. Reproduction of this information with any alteration is an unfair and deceptive business practice. Bridgelux WuXi is not responsible or liable for such altered documentation.

Resale of Bridgelux WuXi's products with statements different from or beyond the parameters stated by Bridgelux WuXi for that product or service voids all express or implied warranties for the associated Bridgelux WuXi's product or service and is unfair and deceptive business practice. Bridgelux WuXi is not responsible or liable for any such statements.

Bridgelux WuXi's products are not authorized for use as critical components in life support devices or systems without the express written approval of Bridgelux WuXi. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.