

Vero[®] SE Series

Bridgelux Differentiation

- 15+ years of driving LED industry transformation
- Our DNA is to solve customer problems
- Broadest portfolio of color points
- First and only LED light source 10 year warranty for Vero[®] Series



Features

- Poke-in connectivity
- No exposed solder pads
- Industry standard 36V
- 65-97 CRI and Class A
- Industry's broadest range of CCT/CRI options
- Industry's highest R9 values on 90 CRI products (up to 74)"

Benefits

- Solderless, connector free installation
- Multiple electrical options to increase design flexibility and reduce driver cost
- Industry standard electrical compatibility
- Single LED brand for all white points
- Higher color quality for differentiated LED light experience



Applications

- Retail & Hospitality
- Architectural & Museums
- Office & Education
- Industrial & Warehouse
- Healthcare
- Entertainment
- Residential
- Food



Product	CCT Range	CRI	SDCM	Typ. Flux* (lm) 3000K, 80CRI	Drive Current (mA)	Voltage* (V)	Efficacy* (lm/W) 3000K, 80CRI	LES (mm)
Vero SE 10B Vero SE 10C Vero SE 10D	1750K-6500K	65, 70, 80, 90, 97 and Class A	1, 2, 3 and 4	1507	270	34.8	160	10
2009				360	34.8			
1459				350	26.0			
2609				450	34.8			
Vero SE 13B Vero SE 13C Vero SE 13D				3653	630	34.8	167	13
				2649	500	31.8		
Vero SE 18B Vero SE 18C Vero SE 18D				5255	900	34.8	168	18
				6832	1170	34.8		
				5109	1050	29.0		
Vero SE 29B Vero SE 29C Vero SE 29D				15872	1800	52.0	170	29
				20124	1710	69.4		
				13390	2100	37.6		

* All measurements are at T_c=25°C